



PUBLIC

SAP Data Services

2022-06-02

DQM Microservices Blueprints User Guide

SAP Data Services 4.3 SP00

Content

- 1 Introduction. 3**
- 1.1 Documentation set for SAP Data Services content objects. 3
- 1.2 SAP information resources. 3
- 1.3 Introduction to SAP Data Services 4.3 content objects. 4

- 2 DQM microservices blueprints overview. 6**

- 3 Before you begin. 7**

- 4 Downloading blueprint packages. 8**
- 4.1 Blueprint versions. 8
- 4.2 Available DQM microservices blueprints. 8
- 4.3 Downloading and setting up blueprints. 8

- 5 Configuring and running jobs. 10**
- 5.1 Editing the datastore. 10
- 5.2 Before running the hybrid job. 11
- 5.3 Decimal separator in the geo job. 12

1 Introduction

1.1 Documentation set for SAP Data Services content objects


You should become familiar with all of the pieces of documentation that relate to the SAP Data Services blueprints and other content objects.

Document	What this document provides
<i>Content Objects Summary</i>	Lists all of the available blueprints and other content objects and the jobs and other objects that they contain.
<i>Data Quality Management Custom Functions User's Guide</i>	Contains instructions for downloading and importing custom functions.
<i>Data Quality Management Match Blueprints User's Guide</i>	Contains a list of available Data Quality Management match blueprints and instructions for downloading, configuring, and running them.
<i>Data Quality Management Directory Expiration Blueprint User's Guide</i>	Contains instructions for downloading and using a blueprint that contains a job with a script that, when configured properly, can send you email notifications for address directories that are nearing their expiration date.
<i>Data Quality Management Microservices Blueprints User's Guide</i>	Contains a list of available Data Quality Management microservices blueprints and instructions for downloading, configuring, and running them.
<i>Data Quality Management Regional Blueprints User's Guide</i>	Contains a list of available Data Quality Management regional blueprints and instructions for downloading, configuring, and running them.

1.2 SAP information resources

A global network of SAP technology experts provides customer support, education, and consulting to ensure maximum information management benefit to your business.

Useful addresses at a glance:

Address	Content
Customer Support, Consulting, and Education services https://support.sap.com/ 	Information about SAP support programs, as well as links to technical articles, downloads, and online forums. Consulting services can provide you with information about how SAP can help maximize your information management investment. Education services can provide information about training options and modules. From traditional classroom learning to targeted e-learning seminars, SAP can offer a training package to suit your learning needs and preferred learning style.

Address	Content
Product documentation https://help.sap.com/docs/SAP_DATA_SERVICES	SAP product documentation.
Product Availability Matrix (PAM) https://userapps.support.sap.com/sap/support/pam	Get information about supported platforms for SAP Data Services. Use the search function to search for Data Services. Click the link for the version of Data Services you are searching for.
SAP Community https://community.sap.com/	Search questions and answers, read the latest blog posts and curated content, connect with experts, and improve your SAP skills. Use the search function to search for Data Services.
Blueprints https://wiki.scn.sap.com/wiki/display/EIM/SAP+Data+Services+Blueprints	Blueprints for you to download and modify to fit your needs. Each blueprint contains the necessary SAP Data Services project, jobs, data flows, file formats, sample data, template tables, and custom functions to run the data flows in your environment with only a few modifications.

1.3 Introduction to SAP Data Services 4.3 content objects

Welcome to SAP Data Services 4.3 Content Objects.

Data Services overview

SAP Data Services delivers a single enterprise-class solution for data integration, data quality, and data profiling that allows you to integrate, transform, improve, and deliver trusted data to critical business processes. It provides one development UI, metadata repository, data connectivity layer, run-time environment, and management console—enabling IT organizations to lower total cost of ownership and accelerate time to value. With SAP Data Services, IT organizations can maximize operational efficiency with a single solution to improve data quality and gain access to heterogeneous sources and applications.

Data Services Content Objects overview

We've identified a number of common scenarios that you are likely to perform with SAP Data Services. For each scenario, we've included a blueprint that is already set up to solve the business problem in that scenario. Each blueprint contains the necessary project, jobs, data flows, file formats, sample data, template tables, and custom functions to run the data flows in your environment with only a few modifications.

You can download the blueprint packages from the SAP Community Wiki. On the website, we periodically post new and updated blueprints, custom functions, best practices, whitepapers, and other content. You can refer to

this site frequently for updated content and use the forums to provide us with any questions or requests you may have.

Instructions for downloading and installing the content objects are also located on the SAP Community Wiki.

2 DQM microservices blueprints overview

SAP Data Quality Management, microservices for location data offers cloud-based microservices for address cleansing, geocoding, and reverse geocoding. You can embed address cleansing and enrichment services within any business process or application so that you can quickly reap the value of complete and accurate address data.

The DQM Microservices transform helps you configure and execute a subset of DQM microservices services within Data Services.

The DQM microservices blueprints illustrate a number of common data quality scenarios that you are likely to perform with SAP Data Services to access functionality in DQM microservices. For each scenario, we've included a blueprint that is configured to solve the business problem in that scenario. Each blueprint contains the necessary project, jobs, data flows, file formats, and sample data to run the jobs in your environment with only a few modifications.

3 Before you begin

Before you start using the DQM microservices blueprints, you or your SAP Business Technology Platform (BTP) administrator will need to perform the following steps.

1. Create a subaccount and enable Data Quality Services within either the Frankfurt Neo (eu2) or Frankfurt AWS (eu10) data center.

For steps to enable Data Quality Services, see the respective Enabling DQM Microservices section in either the [Neo](#) environment or the [Cloud Foundry](#) environment in the Data Quality Management Microservices for Location Data documentation in the SAP Help Portal.

i Note

To use the free plan you must be registered for CPEA or Pay-As-You-Go and must create the subaccount on Frankfurt AWS (eu10). With the free plan, you can process up to 1000 transactions for 30 days, whichever comes first.

2. Obtain the OAuth credentials from the SAP BTP cockpit.

For steps to access the OAuth credentials in the SAP BTP cockpit, see the respective OAuth 2.0 Authorization section in either the [Neo](#) environment or the [Cloud Foundry](#) environment in the Data Quality Management Microservices for Location Data documentation in the SAP Help Portal.

For more information about Data Quality Management Microservices for Location Data, see the documentation on the https://help.sap.com/docs/SAP_Data_Quality_Management_microservices_for_location_data/d95546360fea44988eb614718ff7e959/f62493dd5d824c748e337257c87e2459.html.

4 Downloading blueprint packages

4.1 Blueprint versions

The following table shows the version of the Data Quality Management blueprints that can be used for SAP Data Services. The blueprint version is displayed on the SAP Data Services Blueprints page of the SAP Community Wiki.

SAP Data Services version	Blueprint version	Blueprints available
4.3	4.3	Data Quality Management
4.2	4.2	Data Quality Management

4.2 Available DQM microservices blueprints

Each blueprints package contains sample jobs configured to illustrate an example for how to configure common use cases when using SAP Data Quality Management, microservices for location data within Data Services.

To see the contents of each blueprint, see the *Content Objects Summary*.

Blueprint	Description
Data Quality Management Blueprints – Microservices	Contains jobs configured to illustrate an example for how to configure specific DQM microservices use cases.

4.3 Downloading and setting up blueprints

General steps for downloading and setting up Data Quality Management blueprint packages for SAP Data Services.

Context

Procedure

1. To access the SAP Community Network website, go to <https://www.sdn.sap.com/irj/boc/blueprints>.
2. Log into your account using your username and password, or create a new account.
3. Review the list of available blueprint packages and other content objects and their descriptions to decide which to download.
4. Download and then save the .zip file to the Tutorial Files folder in your installed SAP Data Services path. By default, this folder is installed to \Program Files\SAP BusinessObjects\Data Services \Tutorial Files for 32-bit Windows and \Program Files (x86)\SAP BusinessObjects\Data Services\Tutorial Files for 64-bit Windows.

If you are running on UNIX, the Tutorial Files folder exists only on the Windows client workstation, and you should download the .zip file there.
5. In the Tutorial Files folder in Windows Explorer, right-click the .zip file and select to extract the compressed (zipped) folders to the Tutorial Files folder.
Extracting creates subfolders and places the files in the appropriate location. The .atl file is saved to the Data Quality Mgmt Samples folder, the sample data files are saved to the Data Quality Mgmt Samples\Microservices folder.
6. In the Designer, import the dqm_blueprints_microservices.atl file. In the Passphrase window, enter **dqm_blueprints_microservices** and click *Import*. Click *OK* to close the warning window.
Importing the file adds a project called DataQualityMgmtBlueprintsMicroservices to your object library. The project contains jobs whose names begin with DqmBlueprintMicroservices and contain in their name the Data Quality Management use case that they illustrate. Each job contains a data flow with the same name as the job. The import also adds a datastore called DqmBlueprintsMicroservices to your object library, and file formats whose names begin with DqmMicroservicesIn and DqmMicroservicesOut for the sample input and output data.
7. If you are running on UNIX, copy the input files to the job server machine and create the same folder structure that is on the Windows client workstation.
8. If you imported the blueprint .atl files using a Data Services Designer on 32-bit Windows and use a job server on 64-bit Windows, then you must copy the blueprint files to the Data Services installation of the job server machine.

5 Configuring and running jobs

5.1 Editing the datastore

Prerequisites

To configure the datastore for the DQM Microservices transform, you will need to gather information from your SAP Business Technology Platform (BTP) administrator and your network administrator. For more information about SAP Data Quality Management, microservices for location data, see the documentation set at <https://help.sap.com/viewer/d95546360fea44988eb614718ff7e959/Cloud/en-US>.

Context

After you download the blueprint .zip file to the appropriate folder, unzip it, and import the .atl file in the Designer, you must edit the DqmBlueprintsMicroservices datastore.

Procedure

1. Select the *Datastores* tab of the Local Object Library, right-click the DqmBlueprintsMicroservices datastore and select *Edit*.
2. In the *Edit Datastore DqmBlueprintsMicroservices* window, for Connection URL, replace *CHANGE_THIS* with your Application URL. The Application URL should begin with `https://` and end with `/dq`.
3. In the *Advanced* pane, complete the *Client ID*, *Client Secret*, and *Access Token URL* properties. Leave the *Access Token* property empty. Your SAP Business Technology Platform (BTP) administrator can provide this information.

SAP Data Services data store property	SAP BTP credentials property
Client ID	Client ID
Client Secret	Client Secret
Access Token URL	Token Endpoint

Note

SAP Data Services also supports configuring the data store with the Access Token, but to do this your SAP BTP administrator will have to generate an OAuth 2.0 access token. If you select this option, then

enter the OAuth 2.0 access token in the *Access Token* property, and leave the *Client ID*, *Client Secret*, and *Access Token URL* properties blank.

4. If necessary, enter your proxy information in the *Proxy host* and *Proxy port* options. You can obtain this information from your network administrator.
5. Click *OK*.

Results

After you edit the datastore, you should be able to run the blueprints.

5.2 Before running the hybrid job

Prerequisites

The `DqmBlueprintMicroservices_AddressCleanseHybrid` job illustrates a configuration that cleanses addresses for one country on premise with the Global Address Cleanse transform, and addresses for all other countries in the cloud with the DQM Microservices transform. The scenario is that you do enough business in one country to warrant an on-premise license of address reference data for that country.

Before you run the hybrid job, you must complete the following tasks.

1. Copy the address cleanse reference file for the on-premise country that you have a license for.
2. In the substitution parameter configuration `Configuration1`, in `$$RefFilesAddressCleanse` enter the path location where you copied the address cleanse reference file.
3. (Optional) You may want to add at least one record for the country that you have a license for in the input text file `<DqmMicroservicesInSampleData.txt>`. The sample data used for the hybrid blueprint includes addresses in Brazil, China, Germany, France, India, Japan, Mexico, and the United States. If your on-premise license is for one of these countries, then this step is already completed. If you copied the downloaded compressed file and extracted it in the location specified in [Downloading and setting up blueprints \[page 8\]](#), you will find the input file here:
 - For 32-bit Windows: `\Program Files\SAP BusinessObjects\Data Services\Tutorial Files\Data Quality Mgmt Samples\Microservices`
 - For 64-bit Windows: `\Program Files (x86)\SAP BusinessObjects\Data Services\Tutorial Files\Data Quality Mgmt Samples\Microservices`
4. Edit the job to route addresses for the country that you have a license for to the Global Address Cleanse transform, and addresses for all other countries to the DQM Microservices transform. If your on-premise license is for the United States, then this step is already completed.
 1. Select the *Data Flows* tab of the Local Object Library, and double-click the `DqmBlueprintMicroservices_AddressCleanseHybrid` data flow.
 2. Double-click the Case transform to open it.
 3. In the editable text box you will see the expression `CountryID2Char.COUNTRY = 'US'`, which defaults to the the United States. Change **us** to reference the ISO 2-character country code for your country.

4. Save the data flow.
5. After running the job, you may validate the engine that cleansed each address by looking at the HTTP_STATUS_CODE field in the output file. Records that are cleansed on premise do not receive an HTTP status code; therefore, the content of the field is null. Records that are successfully cleansed in the cloud receive an HTTP status code of 200.

5.3 Decimal separator in the geo job

Context

In some locales it is common to use a decimal point as the decimal separator in latitude and longitude coordinates. For example, 40.689144 and -74.044468. In other locales, it is common to use a decimal comma. For example, 40,689144 and -74,044468.

By default, the DqmBlueprintsMicroservices_AddressCleanseGeo job outputs the latitude and longitude values with a decimal point.

Complete the following steps in order to output the latitude and longitude values with a decimal comma as the decimal separator:

Procedure

1. Go to the *Formats* tab in the local object library of the Data Services Designer.
2. Expand the *Flat Files* tree and right-click on the DqmMicroservicesOutAddressCleanseGeo file format. Click *Edit*.
3. In the *Format* column for the Latitude output field, select *###0,0* from the drop-down menu. Do the same for Longitude.
4. Click *Save* and close the *File Format Editor* window.

Results



After running the DqmBlueprintsMicroservices_AddressCleanseGeo job, the latitude and longitude values in the DqmMicroservicesOutAddressCleanseGeo.txt output file have a decimal comma for the decimal separator.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon : You are leaving the documentation for that particular SAP product or service and are entering a SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2022 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.